Set-Up B

digital

VT102 Set-Up

Use A Pencil To Record The Set-Up Features You Have Selected

Modem

P= T= R=

Modem Control Feature

Turnaround/ Disconnect Character

Printer

P= T/R=

1

- Scroll { 0= Jump, 1= Smooth
- Auto Repeat { 0= Off, 1= On
- Screen { 0= Dark, 1= Light
- Cursor { 0= Underline, 1= Block

2

- Margin Bell { 0= Off, 1= On
- Keyclick { 0= Off, 1= On
- Ansi/VT52 { 0= VT52, 1= Ansi
- Auto Xon/Xoff { 0= Off, 1= On

3

- U.S./U.K. Character Set { 0= U.S., 1= U.K.
- Auto Wrap { 0= Off, 1= On
- Line Feed New Line { 0= Off, 1= On
- Local Echo { 0= Off, 1= On

4

- Print Term.Char. { 0= None, 1= F F
- Print Extent { 0= Scroll Reg., 1= Full Screen
- 1 or 2 Stop Bits { 0= 1 Bit, 1= 2 Bits
- Receive Parity { 0= Ignore, 1= Check

5

- Break Enable { 0= Off, 1= On
- Disconnect Char. Enable { 0= Off, 1= On
- Disc Delay { 0= U.K., 1= Other
- Auto Answbk. Enable { 0= Off, 1= On

6

- Initial Direction { 0= RCV, 1= XMT
- Auto Turnaround { 0= Manual, 1= Auto
- Reserved { Always 0
- Reserved { Always 0

7

- Power { 0= 60 Hz., 1= 50 Hz.
- WPS Term. { 0= Off, 1= On
- Clock { Always 1
- Reserved { Always 0

Answer Back

Tabs

↑ To Increase Screen Brightness
↓ To Decrease Screen Brightness
— 80 Columns Per Line
— 132 Columns Per Line

3618621-01